


# MACHINE TAPES FOR PAPER FOLDING


## Fast Joint

### 2P6 0-0


### NEW!



PREPARATION




HOT MELTING



COOLING



5 min



- **FAST JOINT:** with CHIORINO equipment, in a few minutes the belt is ready for running
- **SOFT SURFACE**
- **HIGH FLEXIBILITY**
- **HIGH RESISTANCE TO ABRASION**
- **IT DOES NOT MARK THE PAPER**
- **SUITABLE FOR HIGH SPEED**

	Polyamide textile carcass	Thermoplastic polyurethane	Polyamide textile carcass	Total thickness [mm]	Weight [kg/m <sup>2</sup> ]	Minimum diameter [mm]	Pull for 1% elongation [N/mm]	Min. and max. temperature resistance [°C]
2P6 0-0				1,8	1,6	20	5	- 20 +100

(1) = Minimum roller diameter is dependent on the joint recommended by CHIORINO.

(2) = Double the value of the pull for 1% elongation to obtain maximum admissible elongation.

**Ideas  
in motion**

CHIORINO S.p.A. - Via S. Agata, 9 - 13900 BIELLA - ITALIA  
Tel. +39-015.8489.1 - Fax +39-015.849.61.61  
www.chiorino.com